TRI-BAND IN-BUILDING ANTENNAS

Comprod In-building antennas are designed to provide excellent coverage solutions in order for external Public Safety Radio Frequencies to propagate within buildings, tunnels or public use environments.

Our antennas can cover single or multiple frequency bands. We offer a wide variety of antennas with Fire Retardant 6200 Kydex radomes. These materials are designed for In-building applications and inside public transport vehicles such as underground trains, vans, buses and trains. They meet the recommended fire safety practices of both the Federal Transit Administration (FTA) and the Federal Rail Administration (FRA) for smoke emission and flammability as tested under ASTM E-662 and ASTM E-162

The F-3741 has been designed for mounting on a concrete surface. This is a requirement for meeting full bandwidth specifications. Polycarbonate tubing is used for the radome on the F-3741. It's a flame resistant and self-extinguishing material. The F-3741 and F-3749 models are also available for the 700 MHz bands.





F-3749

Electrical Specifications	F-3741	F-3749	F-3749A
Frequency Range, MHz	VHF / UHF / 806-960	VHF / UHF / 806-960	VHF / UHF / 806-960
Nominal Gain, dBd	Unity	Unity	Unity
Bandwidth: 2.0:1 VSWR, MHz			
138-174	8	8	8
406-512	64	64	64
764-890	126	126	126
806-960	154	154	154
1800-1990	n/a	n/a	n/a
2400-3000	n/a	n/a	n/a
Polarization	Vertical	Vertical	Vertical
Pattern	Omnidirectional	Omnidirectional	Omnidirectional
Power Rating, Watts Total	50	50	50
Nominal Impedance, Ohms	50	50	50
Radome	Polycarbonate	6200 Kydex	6200 Kydex
Color	Black	White	White
Standard Termination	N Male	N Female	2 foot jumper to N Male

Mechanical Specifications	F-3741	F-3749	F-3749A
Length, inch (mm)	11.25 (286.88)	9.78 (249)	9.78 (249)
Diameter, inch (mm)	0.65 (16.575)	7.0 (178.5)	7.0 (178.5)
Weight, lbs (kg)	N/A	N/A	N/A
Required Minimum Ground Plane Size, in	Included (Required)	14 x 14 (357 x 357)	14 x 14 (357 x 357)

