

Performance: Our premium dual band antennas feature heavy-duty design and excellent performance. Perfect for both voice and data transmission. These antennas are very wide in bandwidth.

Stylish and Durable: These antennas are manufactured using the best corrosion-resistant materials and finishes available. The antenna is low profile, extremely rugged and ideal for commercial applications.

Weatherproof: O-ring seals and overlap construction keep moisture out of the antenna.

Standard Mounting: All base loaded antennas mate with the standard Motorola NMO type mount.



692-75 Series

| Electrical Specifications | | |
|------------------------------|---------------------|---------------------|
| Frequency (Full Band), MHz | 900-930 / 2400-2500 | 900-930 / 2400-2500 |
| Nominal Gain, dBd | 2.0 | 2.0 |
| Bandwidth at 2.0:1 VSWR, MHz | Full Band | Full Band |
| Power Rating, Watts | 250 | 250 |
| Nominal Impedance, Ohms | 50 | 50 |

| Mechanical Specifications | | |
|---------------------------|----------------------------|----------------------------|
| Base | ABS | ABS |
| Contact | Spring-loaded, gold-plated | Spring-loaded, gold-plated |
| Length, in | 3 | 3 |
| Mounting | Standard Motorola NMO type | Standard Motorola NMO type |
| Finish | Brite | Black |
| Ordering Information | 692-75W | 692-75B |