

DUAL BAND ANTENNAS

880-2800MHz

Performance: Our premium dual band antennas feature heavy-duty design and excellent performance. Perfect for both voice and data transmission. These antennas are very wide in bandwidth.

Stylish and Durable: These antennas are manufactured using the best corrosion-resistant materials and finishes available. The antenna is low profile, extremely rugged and ideal for commercial applications.

Weatherproof: O-ring seals and overlap construction keep moisture out of the antenna.

Standard Mounting: All base loaded antennas mate with the standard Motorola NMO type mount.



696-75 Series

Electrical Specifications		
Frequency (Full Band), MHz	880-1200 / 2300-2600	1100-1500 / 2400-2800
Nominal Gain, dBd	Unity	Unity
Bandwidth at 2.0:1VSWR, MHz	Full Band	Full Band
Power Rating, Watts	200	200
Nominal Impedance, Ohms	50	50

Mechanical Specifications		
Radiator	Polyester Coated Brass	Polyester Coated Brass
Base	ABS, Ultrasonic, Brass insert	ABS, Ultrasonic, Brass insert
Contact	Spring-loaded, gold-plated	Spring-loaded, gold-plated
Length, in	2.75	2.75
Mounting	Standard Motorola NMO type	Standard Motorola NMO type
Finish	Black	Black
Ordering Information	696-75B	696-75-1B