VHF EXPOSED DIPOLES WITH REFLECTORS

870 Series VHF Exposed Dipoles with Reflectors

The F-37XX Series antennas are our 870 Series VHF Exposed Dipoles with Reflectors. They are available in 1, 2, 4 dipole configurations. All our antennas can be completely customized to your applications. Our antennas can be black anodized, fully welded, side mount or top mount, and heavy-duty versions are available.

The Reflectors provide a higher degree of directivity. This product is ideal for state or country borders. We have seen great success with being able to shape the RF patterns in the 870-series antenna line.

- Each antenna is configured as a 3/8 wave version.
- The reflectors provide more directivity and greater front-to-back ratios.
- These exposed dipoles have internal cabling and fixed dipole to mast spacing.
- Heavy-duty versions are available. Please contact our Technical Support team for consultation.

| Electrical Specifications | F-3729 | F-3713 | F-3766 | |
|---|-------------|-------------|--------------|--|
| Frequency Range, MHz | 138-174 | 138-174 | 138-174 | |
| Nominal Gain, dBd | 2.5-3.0 | 7.0 | 9.0-10.0 | |
| Number of Dipoles | 1 | 2 | 4 | |
| Number of Reflectors | 7 | 7 | 7 | |
| Bandwidth 1.5:1 VSWR, MHz | 36 | 36 | 36 | |
| Polarization | Vertical | Vertical | Vertical | |
| Pattern | Directional | Directional | Directional | |
| Power Rating, Watts | 200 | 450 | 450 | |
| Nominal Impedance, Ohms | 50 | 50 | 50 | |
| Lightning Protection | DC Ground | DC Ground | DC Ground | |
| Standard Termination | Type N Male | Type N Male | Type N Male | |
| Mechanical Specifications | F-3729 | F-3713 | F-3766 | |
| Length, in (mm) | 72 (1829) | 120 (3048) | 240 (6096) | |
| Width (1/2 Wave Spacing), in (mm) | 50 (1270) | 53 (1346) | 53 (1346) | |
| Weight, lbs. (kg) | 34.3 (15.6) | 57.2 (26) | 100.3 (45.5) | |
| Mounting Information Mast O.D. | 2.4" (61) | 2.4" (61) | 2.9" (73) | |
| * See next page for ordering information (page 3) * | | | | |





Tel: US 1.877.825.2007 / CAN 1.800.603.1454


VHF EXPOSED DIPOLES WITH REFLECTORS

























3/8 wave Spacing Vertical

Simplifying RF Solutions

Tel: US 1.877.825.2007 / CAN 1.800.603.1454



VHF EXPOSED DIPOLES WITH REFLECTORS

138-174 MHz

| Order Information | Side Mount | Top Mount | Black Anodized |
|-------------------|------------|---------------------|----------------|
| F-3729 | F-3729-SM | F-3729-TM | F-3729-SMB |
| F-3713 | F-3713-SM | F-3713-TM | F-3713-SMB |
| F-3766 | F-3766-SM | F-33228 (Mid Mount) | F-3766-SMB |

