

XMF BAND PASS MULTICOUPLER UHF

406-512MHz

60-40-XP Series

Comprod Inc. BandPass, UHF, Multicoupler, filters are designed for minimizing interference from adjacent channels and outside systems. They are available in single, dual, triple or additional units. Selectivity can be determined by the insertion loss of the cavity or by adding cavity units as needed. Each cavity is temperature compensated for operation between -40°C to +60°C. Each cavity has a gold alodine finish, silver plated loops, and silver plated tuning rods. Every cavity is equipped with both coarse and fine tuning rods for quick and easy field or lab re-tuning applications.

- **Temperature Compensation**

- Ensures Frequency Stability

- **High Attenuation**

- Minimizes desense and interference from adjacent systems

- **Adjustable Loops**

- Each cavity has a calibration index



Electrical Specifications	60-40-71	60-40-72	60-40-73
Frequency Range, MHz	406-512	406-512	406-512
Frequency Spacing Min. MHZ	0.8	0.8	0.8
Cavity Diameter, in	6.625	6.625	6.625
Continuous Power Input , Watts (Dependant on Insertion Loss,)	80-300	80-300	80-300
Connectors	N Female	N Female	N Female
Insertion Loss, dB	0.7, 1.2, 3.2	1.2, 2.2	1.7, 3.2
Channel Isolation	See Curves		
VSWR	1.5:1	1.5:1	1.5:1
Temperature °C	-40 to +60	-40 to +60	-40 to +60
Mechanical Specifications	60-40-71	60-40-72	60-40-73
Maximum length, in (H x W X D)	16 x 19 x 7	16 x 19 x 16.5	16 x 19 x 16.5
Weight, lbs (kg)	18 (8.6)	26 (11.8)	32 (15.2)

