

XPANDABLE TRANSMIT COMBINER**132-174MHz****XTC-Xpandable Transmit Combiner Series—10" Cavity**

Our eXpandable Transmit Combiners can combine from 1 to 21 channels. The XTC series of filters incorporates expandability, close frequency spacing and some of the lowest insertion losses in the industry. Using a 6.625" cavity, the XTC can easily support 75 kHz Tx-Tx spacing or 50 kHz spacing while using 10" cavities. Each cavity is constructed using a gold alodine finish, silver plated loops, silver plated connectors and internal tuning plunger. Additionally, cavities are temperature compensated for operation between -40°C to +60°C. Every cavity is equipped with both coarse and fine tuning rods for quick and easy field or lab re-tuning.

- Flexible and expandable design, From 1-21 channel capacity
- Expandable 1 or more additional channels at a time, Re-configurable equipment
- 132-174 MHz, 42 MHz of operating bandwidth
- Temperature compensation, Ensures frequency stability
- High Attenuation, Minimizes desense and interference
- Ultra-low insertion losses, Low coupling and bridging losses
- Continuous high power handling capability, 150 watts – 24/7



Electrical Specifications	XTC-13-02	XTC-13-04	XTC-13-06	XTC-13-08	XTC-13-0-10	XTC-13-0-12
Frequency Range, MHz	132-174	132-174	132-174	132-174	132-174	132-174
Bandwidth, MHz	42	42	42	42	42	42
Number of Channels	2	4	6	8	10	12
Cavity Diameter, in	10	10	10	10	10	10
Min. Channel Sep., KHz	50	50	50	50	50	50
Isolation Min., Tx-Tx, dB	70	70	70	70	70	70
Isolation Min., Ant-Tx, dB	60	60	60	60	60	60
Max. Insertion Loss Per Chan., dB	4.1	5.0	5.4	5.7	5.9	6.1
Continuous Power Input, Watts	150	150	150	150	150	150
Connectors	N Female	N Female	N Female	N Female	N Female	N Female
VSWR	1.22:1	1.22:1	1.22:1	1.22:1	1.22:1	1.22:1
Temperature °C	-40 to +60	-40 to +60	-40 to +60	-40 to +60	-40 to +60	-40 to +60
Mechanical Specifications	XTC-13-02	XTC-13-04	XTC-13-06	XTC-13-08	XTC-13-0-10	XTC-13-0-12
Height, in (H x W X D) (mm) - (In X Rack)	86.5 x 24 x 40.25 (2197 x 610 x 1022)					
Mounts in 19" Standard Rack	Yes	Yes	Yes	Yes	Yes	Yes
Weight	DEPENDS ON SET-UP AND RACK DESIGN					
Order Information	Single Cavity	2 - Channel	3 - Channel	5 - Channel	8 - Channel	
4" Cavity	XTC-06-41	XTC-06-42	XTC-06-43	XTC-06-45	XTC-06-48	
6.625" Cavity	XTC-06-71	XTC-06-72	XTC-06-73	XTC-06-75	XTC-06-78	
10" Cavity	XTC-06-01	XTC-06-02	XTC-06-03	XTC-06-05	XTC-06-08	