TRI-BAND IN-BUILDING ANTENNAS

Our In-building antennas are designed to provide excellent coverage solutions in order for external Public Safety Radio Frequencies to propagate within buildings, tunnels or public use environments.

Our antennas can cover single or multiple frequency bands. We offer a wide variety of antennas with Fire Retardant 6200 Kydex radomes. These materials are designed for In-building applications and inside public transport vehicles such as underground trains, vans, buses and trains. They meet the recommended fire safety practices of both the Federal Transit Administration (FTA) and the Federal Rail Administration (FRA) for smoke emission and flammability as tested under ASTM E-662 and ASTM E-162.



F-3749-B

The F-3749/A/B antennas are available in custom colors for orders of 150 or more.

			F-3749-B	
Electrical Specifications	F-3749	F-3749 F-3749A		
Frequency Range, MHz	VHF / UHF / 760-960	VHF / UHF / 760-960	VHF / UHF / 760-960	
Nominal Gain	Unity	Unity	Unity	
Bandwidth: 2.0:1 VSWR, MHz				
138-174	8	8	8	
406-512	64	64	64	
764-890	126	126	126	
806-960	154	154 154		
1800-1990	n/a	n/a	n/a	
2400-3000	n/a	n/a	n/a	
Polarization	Vertical	Vertical	Vertical	
Pattern	Omnidirectional	Omnidirectional	Omnidirectional	
Power Rating, Watts Total	50	50	50	
Nominal Impedance, Ohms	50	50	50	
Radome	6200 Kydex	6200 Kydex	6200 Kydex	
Mean Time Between Failure, Hours	87,000	87,000	87,000	
Color	White	White	White	
Standard Termination	N Female	2 foot jumper to N Male	N Female	
Mechanical Specifications	F-3749	F-3749A	F-3749-B	
Length, inch (mm)	9.78 (249)	9.78 (249)	9.78 (249)	
Diameter, inch (mm)	7.0 (178.5)	7.0 (178.5)	7.0 (178.5)	
Weight, lbs (kg)	4 (1.8)	4 (1.8)	4 (1.8)	
Required Minimum Ground Plane Size, in (mm)	14 x 14 (357 x 357) Not Included, see next page for options	14 x 14 (357 x 357) Not Included, see next page for options	14 x 14 (357 x 357) Not Included, see next page for options	




Fax: 1.800.554.1033

TRI-BAND ANTENNAS

F-3749 Top and Underside View










Our In-building antennas require a ground plane to work properly. The minimum ground plane size is specified for each antenna. Failure to provide the ground plane may result in poor propagation and/or poor frequency coverage.

F-3749-B Top and Underside View



Specifications	F-33034	F-33220	F-33135	F-33203	F-33159	F-33105
Fits Antennas	F-3749/A/B	F-3749/B	F-3749/A/B	F-3749/A/B	F-3749/A/B	F-3749/A/B
Ground Plane in	14x14	14x14	24x48	24x24	12x26	14x14
Included with Antenna	No	No	No	No	No	No
Length, in	~16	~16	24	24	12	14
Width, in	14	14	48	24	26	14x5.625







F-33220 Mounting Bracket



Tel: US 1.877.825.2007 / CAN 1.800.603.1454 Email: sales@comprodcom.com

Fax: 1.800.554.1033