



Radome Yagi Antennas Series

The Radome Yagi Antenna Series are available in UHF and 700/800/900 MHz configurations. The UHF model is offered with a Fiberglass or PVC Radome. The 700/800/900 MHz model is offered in PVC. All our antennas can be completely customized to your particular applications.


- Each antenna has a rugged design to withstand extreme environmental conditions.
- The mounting hardware supplied supports either vertical or horizontal polarization.
- DC ground for lightning protection.
- The PVC enclosure is 1/2 inch thick.
- The PVC radome models are our Heavy-Duty Versions.
- This antenna is available in Low-PIM (-150 dBc; two 20W carriers).


490-70-HDR

Electrical Specifications	425-70-HDR	426-70-R	490-70-HDR
Frequency Range, MHz (in splits)	406-470	406-470	746-960
Nominal Gain, dBd	10	10	10
Number of Elements	7	7	7
Bandwidth: 1.5:1 VSWR, MHz	20	20	72
Polarization	Vert./Hor.		
Horizontal Beamwidth (Horizontal Pol.)	62°	62°	56°
Vertical Beamwidth (Horizontal Pol.)	480	480	42°
Front to Back, dB	20	20	20
Pattern	Directional		
Power Rating, Watts	250	250	150
Nominal Impedance, Ohms	50	50	50
Lightning Protection	DC Ground		
Standard Termination	Type N- Female for standard version		
Mechanical Specifications	425-70-HDR	426-70-R	490-70-HDR
Length, in (mm)	31 (787)	30 (762)	29 (737)
Martin Co.			
Width, in (mm)	16 (406)	16 (406)	14 (356)
Weight, Ibs. (kg)	16 (406) 44 (20)	16 (406) 19 (8.6)	14 (356) 28 (12)
, , ,	. ,		
Weight, lbs. (kg)	44 (20)	19 (8.6)	28 (12)
Weight, lbs. (kg) Radome Material	44 (20) PVC	19 (8.6) Fiberglass	28 (12) PVC
Weight, lbs. (kg) Radome Material Rated Wind Velocity, No Ice, mph (km/h) Rated Wind Velocity, 0.5" (13mm) ice, mph	44 (20) PVC 150 (241)	19 (8.6) Fiberglass 120 (193)	28 (12) PVC 150 (241)
Weight, lbs. (kg) Radome Material Rated Wind Velocity, No Ice, mph (km/h) Rated Wind Velocity, 0.5" (13mm) ice, mph (km/h)	44 (20) PVC 150 (241) 105 (169)	19 (8.6) Fiberglass 120 (193) 110 (177)	28 (12) PVC 150 (241) 115 (185)
Weight, lbs. (kg) Radome Material Rated Wind Velocity, No Ice, mph (km/h) Rated Wind Velocity, 0.5" (13mm) ice, mph (km/h) Lateral Thrust @ 100 mph, wind, lbs. (kg)	44 (20) PVC 150 (241) 105 (169) 69 (31.3)	19 (8.6) Fiberglass 120 (193) 110 (177) 61 (27.7)	28 (12) PVC 150 (241) 115 (185) 47.4 (21.5)


RADOME YAGI ANTENNA









425-70-HDR Horizontal pattern (Vertical Polarization) 425-70-HDR Vertical Pattern (Vertical Polarization)









426-70-R Horizontal pattern (Vertical Polarization)

426-70-R Vertical Pattern (Vertical Polarization)









490-70-HDR Vertical Pattern (Vertical

