





Parabolic Reflector Series Antennas

The Reflector antenna is a SRSP-507 Category A compliant antenna. These antennas have a very high front-to-back ratio. They are broadband and are ideal for point-to-point applications where restrictions on beam width are present. Performance is constant throughout the band.

- · Mechanical resonance reducing design.
- Each antenna has a rugged design to withstand harsh environmental conditions.
- The 965-70 is a highly-directive parabolic antenna consisting of a back-firing dipole reflector assembly for increased gain and directivity.
- These antennas have ultra-low VSWR ratings and will not exceed 1.5:1 VSWR ratio with 0.5" of radial ice.
- The mounting hardware supplied will permit either vertical or horizontal polarization. DC ground for lightning protection. Black Anodized and Dipole Radome protected versions are available.
- This antenna is available in Low-PIM (-150 dBc; two 20W carriers).
- Please contact our Technical Support team for consultation.

Electrical Specifications	965-70-HD	965-70-HDB	965-70-HDBR	
Frequency Range, MHz (in splits)	764-960	764-960	764-960	
Nominal Gain, dBd	16.5	16.5	16.5	
Bandwidth: 1.5:1 VSWR, MHz	72	72	72	
Front to Back, dB	25	25	25	
Pattern	Directional			
Power Rating, Watts	200	200	200	
Nominal Impedance, Ohms	50	50	50	
Lightning Protection	DC Ground			
Standard Termination	Type N Male for standard version – DIN 7/16 or 4.3/10 for Low-PIM version			

Mechanical Specifications	965-70-HD	965-70-HDB	965-70-HDBR
Length, in (mm)	68 (1727)	68 (1727)	68 (1727)
Width, in (mm)	36 (914)	36 (914)	36 (914)
Weight, lbs. (kg)	49 (22.3)	49 (22.3)	51 (23.2)
Rated Wind Velocity, No Ice, mph (km/h)	110 (177)	110 (177)	110 (177)
Rated Wind Velocity, 0.5" (13mm) ice, mph (km/h)	85 (137)	85 (137)	85 (137)
Lateral Thrust @ 100 mph, wind, lbs. (kg)	1.9 (0.46)	1.9 (0.46)	1.9 (0.46)
Projected Area, ft ² (m ²)	4.9 (0.46)	4.9 (0.46)	5 (0.47)
Mounting Hardware Included	112-85 Clamp	112-85 Clamp	112-85 Clamp

















